

KS



KS 1200

Functioneel LED plafond- en wandarmatuur met semi-opalen PMMA afscherming. Basis uit witgelakte staalplaat. In optie DALI- of analoog (1-10V) dimbaar.

| Productcode | Omschrijving |
|------------------|-----------------------------------|
| KS1200200083 | KS 1200 LED 2500lm 20W 3000K |
| KS1200400083 | KS 1200 LED 5000lm 41W 3000K |
| KS1200400083IP44 | KS 1200 LED 5000lm 41W 3000K IP44 |
| KS1200400084 | KS 1200 LED 5000lm 41W 4000K |
| KS1200400084IP44 | KS 1200 LED 5000lm 41W 4000K IP44 |
| KS1200800083 | KS 1200 LED 7500lm 65W 3000K |
| KS1200800083IP44 | KS 1200 LED 7500lm 65W 3000K IP44 |
| KS1200800084 | KS 1200 LED 7500lm 65W 4000K |
| KS1200800084IP44 | KS 1200 LED 7500lm 65W 4000K IP44 |
| KS1500700083 | KS 1500 LED 7300lm 63W 3000K |
| KS1500700083IP44 | KS 1500 LED 7300lm 63W 3000K IP44 |
| KS1500700084 | KS 1500 LED 7300lm 65W 4000K |
| KS1500700084IP44 | KS 1500 LED 7300lm 65W 4000K IP44 |
| KS600200083 | KS 600 LED 2500lm 21W 3000K |
| KS600200083IP44 | KS 600 LED 2500lm 21W 3000K IP44 |
| KS600200084 | KS 600 LED 2500lm 21W 4000K |
| KS600200084IP44 | KS 600 LED 2500lm 21W 4000K IP44 |