

## KS



KS 1200

Functioneel LED plafond- en wandarmatuur met semi-opalen PMMA afscherming. Basis uit witgelakte staalplaat. In optie DALI- of analoog (1-10V) dimbaar.

Productcode	Omschrijving
KS1200200083	KS 1200 LED 2500lm 20W 3000K
KS1200400083	KS 1200 LED 5000lm 41W 3000K
KS1200400083IP44	KS 1200 LED 5000lm 41W 3000K IP44
KS1200400084	KS 1200 LED 5000lm 41W 4000K
KS1200400084IP44	KS 1200 LED 5000lm 41W 4000K IP44
KS1200800083	KS 1200 LED 7500lm 65W 3000K
KS1200800083IP44	KS 1200 LED 7500lm 65W 3000K IP44
KS1200800084	KS 1200 LED 7500lm 65W 4000K
KS1200800084IP44	KS 1200 LED 7500lm 65W 4000K IP44
KS1500700083	KS 1500 LED 7300lm 63W 3000K
KS1500700083IP44	KS 1500 LED 7300lm 63W 3000K IP44
KS1500700084	KS 1500 LED 7300lm 65W 4000K
KS1500700084IP44	KS 1500 LED 7300lm 65W 4000K IP44
KS600200083	KS 600 LED 2500lm 21W 3000K
KS600200083IP44	KS 600 LED 2500lm 21W 3000K IP44
KS600200084	KS 600 LED 2500lm 21W 4000K
KS600200084IP44	KS 600 LED 2500lm 21W 4000K IP44